

GF LITHIUM EXTREME PRESSURE GREASE (EP 0)

GF Lithium EP-0 stands out as a top-tier semi-fluid grease, formulated with premium lithium and fortified with extreme pressure additives. Tailored for centralized lubrication systems, particularly in automotive chassis applications, it guarantees superior performance. With a wide operational temperature span, ranging from -20°C to 120°C, it ensures reliable lubrication across various condition

FEATURES & BENEFITS

- Automotive applications under heavy loads
- Its resistance to water washout makes this grease particularly suitable for equipment where moist or wet conditions are common.

APPLICATIONS

Lubricating gear boxes where excessive leakage of gear oil can cause economic and environmental problems.

SPECIFICATIONS

NLGI: 0, DIN 51502/51825; KP 0K-20

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Thickener Type			Lithium
NLGI Classification			0
Color	Visual	-	Amber
Drop Point	ASTM D566	°C	-
Worked Penetration @25oC, 60 Strokes	ASTM D217	0.1mm	355-385
Oxidation Stability @99 oC for 100 Hrs	ASTM D942	Psi	7(max.)
Base Oil Viscosity @40 oC	ASTM D445	cSt	120-150
Four Ball Weld Load,	ASTM D2596	Kgs	200(min.)
Wear Scar Dia,	ASTM D2266	mm	0.7(max.)

Note: We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

Health and Safety Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Safety Data Sheet (SDS) are followed. SDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment